

## Semi-Paste 1700

- Removes Even the Toughest Coatings in Minutes
- Ideal for Vertical Surfaces
- 25-45 sq. ft./gal

### PRODUCT DESCRIPTION

Semi-Paste 1700 Paint Stripper is a thick paint stripper, slightly thinner than our Semi-Paste so that it can be sprayed. Semi-Paste 1700 can be applied by hand, using either a roller or paint brush to put the paint remover on, or it can be applied using a sprayer that is approved for this type of chemical. It can strip through multiple coats of paint and other tough finishes very quickly, many times within the first few minutes. This paint remover works great on vertical surfaces where a thick product is necessary to keep it from running. Semi-Paste 1700 works great on lead based paint, and has been used onsite on jobs like window and door trim refinishing, stripping paint off of brick, removing graffiti from concrete walls, and many large scale projects. This product can be rinsed off with either water, lacquer thinner or denatured alcohol.

### PROPERTIES

**State:** Liquid  
**Appearance:** Translucent  
**Color:** Colorless/Pale Amber  
**Odor:** Characteristic Penetrating Chloroform  
**Viscosity:** Moderately Thick  
**pH:** Alkaline 11-12.5  
**Chlorinated:** Yes  
**Dilutable:** No  
**Weight:** 10.100 lbs/gal  
**Rinsable:** Yes  
**Organic:** Yes  
**Boiling Point:** 104°F  
**Solubility in Water:** 15%  
**Evaporation Rate:** (BAc = 1) 0.7 (Approximate)



### DIRECTIONS

1. Shake container well and pour liquid into another container. Glass, approved HDPE plastics, or stainless would be most preferable.
2. With a brush or approved sprayer, apply a liberal coat of stripper (approx. 1/8" thick) to the item being stripped. If using a brush, brush in one direction only and try not to over-brush the area.
3. Depending on the nature and age of the coating, results may be visible from 30 seconds to 25 minutes. We suggest picking a small area to test strip (1-2 sq. ft.) to determine the dwell time required to finish the job. Do not allow the stripper to dry out. If this occurs, re-apply more stripper and watch more closely.
4. With a scraper or power washer, remove the coating's remnants and dispose of properly. Please refer the MSDS to your local waste company to decide how this can be done. A water-rinse will neutralize the stripper. Some people, however, like to rinse with another solvent or lacquer thinner depending on the job. If recoating the surface, allow at least 48 hours for the solvents to evaporate and test a small area before coating the entire surface.

(314)266-4600

(844)266-4600

www.MasticRemover.com

Express Chem LLC  
2101 Clifton Avenue,  
Saint Louis, MO 63139

