

MA-33 Low Odor

- High Performance at a Low Cost
- **An Asbestos Contractor Favorite**
- **approx. 125 sq. ft./gal**

PRODUCT DESCRIPTION

Our MA-33 Low Odor Mastic Remover is designed for removing black mastics typically found under vinyl asbestos tile (VAT) and vinyl composite tile (VCT). An asbestos abatement contractor favorite, this mastic remover is used in floor tile removal projects to liquify the left over mastic in just minutes. With a flash point over 142° and a very low odor, MA-33 Low Odor Mastic Remover meets the most common standards for use in commercial buildings.

PROPERTIES

- State:** Liquid
- Appearance:** Clear
- Color:** Colorless/Pale Amber
- Odor:** Low Solvent Odor
- Viscosity:** Very Thin
- pH:** Slightly Acidic in water
- Chlorinated:** No
- Dilutable:** No
- Weight:** 6.63 lbs/gal
- Rinsable:** Yes
- Organic:** Yes
- Boiling Point:** 340°F - 415°F
- Solubility in Water:** 5.1%
- Evaporation Rate:** (Ether = 1) 0.08 (Approximate)

DIRECTIONS

1. Apply MA-33 directly to exposed adhesive by either manually pouring or spraying with a low pressure garden sprayer.
2. Allow 25-35 min for remover to penetrate and soften mastic.
3. After the adhesive has softened, remove with long handled scrapper, broom, or squeegee. Scrape the mastic into a pile or puddle and remove using absorbents, plastic shovels, or explosion-proof wet vacuums.
 - ✧ Stubborn areas or acrylic (brown) mastics may require more aggressive mechanical agitation with a long handle scraper.
4. Rinse the surface with water and detergent to remove any residual product or liquefied mastic.
 - ✧ Porous surfaces may require special care in rinsing to ensure all the solvent is emulsified (this will also aid in preparing the surface for new mastic adhesive)
5. Dispose of waste material according to all federal, state, county, and local regulations.

(314)266-4600
(844)266-4600

www.MasticRemover.com

Express Chem LLC
2101 Clifton Avenue,
Saint Louis, MO 63139

